



TECHNICAL DATA

WEXPEDITE Floor Stripper

Designed for rapid removal of metal interlock polymer, co-polymer and hybrid polymer finishes

APPEARANCE: TRANSPARENT YELLOW LIQUID

ODOR: LIGHT SASSAFRAS

SPECIFIC GRAVITY: 1.037

pH OF CONCENTRATE: 11.6 ± 0.3

pH of 1:4 dilution in tap water: 11.1 ± 0.2

pH of 1:8 dilution in tap water: 10.9 ± 0.2

AMMONIA CONTENT: NONE

PHOSPHATE: NONE

SILICATE: NONE

BUTYL CELLOSOLVE: NONE



325 Leffingwell Avenue • Kirkwood, Missouri

www.wexfordlabs.com

(800) 506-1146

WEXPEDITE

FLOOR FINISH REMOVER

Contains No Butyl Cellusolve – Non-Ammoniated

Wexpedite floor finish remover is designed for the rapid removal of metal interlock, polymer, and co-polymer finishes and all waxes.

DIRECTIONS FOR USE

METAL INTERLOCK FINISHES:

Use **WeXpedite** floor stripper at a dilution of 1:4 (one quart of **WeXpedite** to each gallon of water). Thoroughly wet floors with stripping solution for 5 to 15 minutes. Agitate as necessary with stripping pad, or scrubbing pad or brush to completely loosen and emulsify the old finish. Pick up used solution with wetvac, squeegee and pan, or mop and rinse floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying new finish.

POLYMER AND CO-POLYMER:

Use **WeXpedite** floor stripper at a dilution of 1:8 (one pint of **WeXpedite** to each gallon of water). Thoroughly wet floor with stripping solution for 3 to 10 minutes. Agitate as necessary with stripping pad, or scrubbing pad or brush to completely loosen and emulsify old finish. Pick up solution with wetvac, squeegee and pan or mop and rinse floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying a new finish.

WAXES:

Use **WeXpedite** floor stripper at a dilution of 1:8 (one pint of **WeXpedite** to each gallon of water). Thoroughly wet floor with stripper solution for 3 to 10 minutes. If wax is very old agitation with a scrubbing pad or brush may be required near walls, under furniture or in other non-traffic areas. When old wax is completely emulsified, pick up used stripper solutions with wetvac, squeegee and pan or mop. Rinse the floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying new wax or finish.

CAUTION: Protect eyes from **WeXpedite** concentrate and avoid prolonged contact with the skin. Provide adequate ventilation. Contains primary amines and cyclohexanol. Flush eyes or skin with large amounts of water if exposed, and contact a physician.



325 Leffingwell Avenue • Kirkwood, Missouri

www.wexfordlabs.com

(800) 506-1146