



TECHNICAL DATA

WEX-STRIP

Floor Stripper

APPEARANCE.....	Transparent blue liquid
ODOR	Light Sassafras
pH of USE SOLUTION	12.0 ± 0.3
AMMONIA CONTENT	NONE

LABEL INFORMATION:

Label must clearly state that product is designed for removal of:

1. METAL INTERLOCK floor finishes
2. POLYMER and CO-POLYMER floor finishes
3. ALL WAXES

LABEL INSTRUCTIONS:

Label must give specific instructions for removal of:

1. METAL INTERLOCK floor finishes
2. POLYMER and CO-POLYMER floor finishes
3. ALL WAXES

WexfordLabs
The Disinfectant Solution

325 Leffingwell Avenue • Kirkwood, Missouri

www.wexfordlabs.com

(800) 506-1146

WEX-STRIP

FLOOR STRIPPER

FAST – EFFECTIVE – BIODEGRADABLE

Wex-Strip is designed for the rapid removal of metal interlock, polymer, and co-polymer finishes and all waxes.

- **METAL INTERLOCK FINISHES**

Use WEX-STRIP Floor Stripper at a dilution of 1:4 (one quart of WEX-STRIP to each gallon of water). Thoroughly wet floors with stripping solution for 5 to 15 minutes. Agitate as necessary with stripping pad, or scrubbing pad or brush to completely loosen and emulsify the old finish. Pick up used solution with wetvac, squeegee and pan, or mop and rinse floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying new finish.

- **POLYMER and CO-POLYMER**

Use WEX-STRIP Floor Stripper at a dilution of 1:8 (one pint of WEX-STRIP to each gallon of water). Thoroughly wet floors with stripping solution for 3 to 10 minutes. Agitate as necessary with stripping pad, or scrubbing pad or brush to completely loosen and emulsify the old finish. Pick up used solution with wetvac, squeegee and pan, or mop and rinse floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying new finish.

- **WAXES**

Use WEX-STRIP Floor Stripper at a dilution of 1:8 (one pint of WEX-STRIP to each gallon of water). Thoroughly wet floors with stripping solution for 3 to 10 minutes. If wax is very old agitation with a scrubbing pad or brush may be required near walls, under furniture or in other non-traffic areas. When old wax is completely emulsified, pick up used stripper solution with wetvac, squeegee and pan, or mop. Rinse the floor thoroughly with clean water. Keep floor wet during total stripping and rinsing operation. Allow floor to dry completely before applying new wax or finish.



325 Leffingwell Avenue • Kirkwood, Missouri

www.wexfordlabs.com

(800) 506-1146